



MicroCom XR 10-Bay Battery Charger

Product Specifications

Charger Models: PBT-10BAY

Overview

We at Pliant® Technologies want to thank you for purchasing the MicroCom 10-Bay Battery Charger. The charger's design allows users to simultaneously charge up to ten Pliant rechargeable lithium-polymer (BT-12) batteries.

Key Features

- Charge up to ten lithium-polymer (BT-12) batteries simultaneously
- Recharge batteries from empty in approximately 3 hours
- LED indicators provide real-time charge status
- Region-specific power cable (included)
- Non-Reflective, textured matte finish
- Full One-Year Parts and Labor Warranty

What's in the Box?

- | | |
|-------------|---------------------------------|
| • PBT-10BAY | Battery Charger |
| • 00004239 | Power Supply |
| • PC-PWR-XX | AC Power Cord (Region Specific) |
| • D0000732 | Operating Guide |

Specifications*

PBT-10BAY	
Input Voltage Range	AC 100 ~ 240V 50/60HZ
Non-Operating Temperature	-10°C to 45°C (14°F to 113°F);
Dimensions (Charger alone) (L×W×H)	157 × 45.2 × 86 mm (6.2 × 1.8 × 3.4 in.)
Weight (with power supply)	400 g (0.88 lb)



PBT-10BAY Battery Charger
(Batteries Not Included)

Pliant Technologies, LLC
CrewCom®
205 Technology Parkway
Auburn, Alabama 36830 USA
www.plianttechnologies.com
Phone +1.334.321.1160
Toll-Free 1.844.475.4268 or 1.844.4PLIANT
Fax +1.334.321.1162

* **Notice About Specifications:** While Pliant makes every attempt to maintain the accuracy of the information contained in this document, this information is subject to change without notice. Please check our website for the latest system specifications and certifications.

Copyright ©2026 Pliant Technologies, LLC. All rights reserved. The Pliant® and CrewCom® word marks and the Pliant "P" logo are trademarks of Pliant Technologies, LLC. All other trademarks are property of their respective owners.